Rushlight Micro

Technical specification / MEYE

Contents

Select a section or page number to jump to it. Use Contents in the footer to return.

01 Product overview 2

02 Light & electrical 3

03 Mechanical & construction 3

04 Service & circularity 3

05 Product FAQs 4

Generated from current saved product details, specification notes and published FAQs. Downloaded copies are dated snapshots. Regenerate after changes. Unanswered fields are omitted. Check suitability for your project before installation.

01 Product overview

Rushlight Micro

Product code	MEYE
Product reference	10038
Rated power (standard LED)	1.6 W
Ingress protection	IP68
Standard cable length	2.00 m
Standard weight	155 g
Warranty period	10 years

Product record updated: 2026-09-09 18:51:49

Specification notes revision: 0

02 Light & electrical

Available LED options (colour / power)	2700K warm white; Monochromatic amber (1.6 W nominal LED)
Nominal LED power	1.6 W
Supply / wiring	DC supply; parallel wiring with parallel protection circuit
2700K warm white supply current / input power	12V DC: 0.16 A / 1.92 W 15V DC: 0.12 A / 1.80 W 24V DC: 0.07 A / 1.68 W
Monochromatic amber supply current / input power	12V DC: 0.13 A / 1.56 W 15V DC: 0.11 A / 1.65 W 24V DC: 0.06 A / 1.44 W
Electrical measurement notes	Supply current is measured; input power is calculated as voltage multiplied by current. Nominal LED wattage is separate from supply input power. Figures apply to the US parallel-protection build.

03 Mechanical & construction

Body material by finish	Hand aged brass: CNC machined Brass CZ121
Available finishes	Hand aged brass

04 Service & circularity

TM66 assessment score	2.6

05 Product FAQs

Which LED colors are available in the U.S.?

For the U.S. range, you can choose 2700K warm white or monochromatic amber. Select your preferred LED color when configuring the light.